

Evaluation of Tracking Algorithms Using Heterogeneous Technologies

EU funded project:




Network of Excellence in Wireless COMMUNICATIONS

Workpackage WPR.B:
"Localization and Positioning"

Francesco Sottile⁽¹⁾, Maurizio A. Spirito⁽¹⁾,
Pau Closas⁽²⁾, Javier Arribas⁽²⁾, Carles Fernández⁽²⁾,
Montse Nájara⁽³⁾, Eva Lagunas⁽³⁾,
Davide Dardari⁽⁴⁾, Nicolò Decarli⁽⁴⁾,
Andrea Conti⁽⁵⁾, Matteo Guerra⁽⁵⁾


Partners:




⁽¹⁾Istituto Superiore Mario Boella (ISMB), Italy.
⁽²⁾Centre Tecnològic de Telecomunicacions de Catalunya (CTTC), Spain.
⁽³⁾Universitat Politècnica de Catalunya (UPC), Spain.
⁽⁴⁾University of Bologna (CNIT-BO), Italy
⁽⁵⁾University of Ferrara (CNIT-FE), Italy

Environment, Mobile Target, Matlab GUI


Indoor Office Environment



Matlab GUI



Mobile Target



Max Speed: 0.44 m/sec

CC2420 ZigBee Module




$\Delta T_{RSS} = 50$ m sec

Accel. Module

IMOTE2 Sensor Board ITS400

$\Delta T_{Accel} = 2$ m sec



3-axis accelerometer
LIS3L02DQ

PulsOn220 UWB Module




$\Delta T_{UWB} = 500$ m sec

Algorithms Tested Using Hybrid Data: ZigBee-RSS, UWB-dist, Acc.


- EKF (Extended Kalman Filter)
- EKF-BT (EKF Bias Tracking)
- PF (Particle Filter)
- CRPF (Cost Reference PF)
- CKF (Cubature Kalman Filter)

Performance

Constant Speed, Reduced Set of Anchors



Variable Speed, Reduced Set of Anchors



GLOBECOM 2010, Miami, Florida, USA
December 8, 2010